

The background of the entire image is a close-up, vertical view of a wood grain. The grain lines are dark and run vertically, creating a textured, organic pattern. The color of the wood is a warm, medium brown. The text is centered horizontally and vertically on the page.

zen

trade & consulting

**WOOD FLOORING
PRODUCTION FACTORY**

COMPANY PROFILE

Produced according to DIN EN 13489 standard, 5G-C click-drop down 3-layer engineered oak floor. Lively rustic character with structure and color differences. Featuring sapwood and natural knot content. Distinct black filled core columns and knots - handscrapped



Wooden floor oak planks 3-layer rustique 5G

Produced according to DIN EN 13489 standard, 5G-C click-drop down 3-layer engineered oak floor. Lively rustic character with structure and color differences. Featuring sapwood and natural knot content. Distinct black filled core columns and knots - handscrapped.

pure oiled

DESCRIPTION	
Length	1900 mm
Width	190 mm
Thickness	14 mm



Wooden floor oak planks 3-layer Provence 5G

Sustainable and produced according to DIN EN 13489 standard, Valinge 5G-C click-drop down 3-layer engineered oak floor. In principle, lively textured with knot content and sapwood. Featuring color differences, brown filler and wax oil.

wax oiled

brown filler

DESCRIPTION	
Length	2100 mm
Width	190 mm
Thickness	14 mm



Wooden floor oak planks 3-layer, Noblesse 5G

Produced according to DIN EN 13489 standard, Valinge 5G-C click-drop down 3-layer engineered oak floor. In principle, naturally textured with small knot content and sapwood. Featuring slight color differences and 3mm top layer.

brushed

unfinished

DESCRIPTION	
Length	1900 mm
Width	190 mm
Thickness	14 mm



It is recommended that you purchase 5-10% more than you need for re-sorting and installation.



Solid oak fishbone planks, rustic

High quality, sustainable herringbone oak floor offers a blend of traditional and modern design. Features rich knot content and approximately 15-20% of sapwood. This is our standard width and the thickness is recommended for underfloor heating.

unfinished

DESCRIPTION	
Length	500-900 mm
Width	120 mm
Thickness	15 mm



quantity may vary up to +/- 0.01m² due to packaging purposes. It is recommended that you purchase 5-10% more than you need for re-sorting and installation.



Solid oak fishbone planks, marcant

High quality, sustainable herringbone oak floor offers a blend of traditional and modern design. Offering a rich surface texture and natural oak color. Features larger knots and sapwood content. This is our standard width and the thickness is recommended for underfloor heating.

unfinished

DESCRIPTION	
Length	500-900 mm
Width	120 mm
Thickness	15 mm



Quantity may vary up to +/- 0.01m² due to packaging purposes. It is recommended that you purchase 5-10% more than you need for re-sorting and installation.



Solid oak fishbone planks, nature

High quality, sustainable herringbone oak floor offers a blend of traditional and modern design. Offering an exquisite light color and delicate texture. Features knot content and is free of sapwood.

unfinished

DESCRIPTION	
Length	500-900 mm
Width	120 mm
Thickness	20 mm



quantity may vary up to +/- 0.01m² due to packaging purposes. It is recommended that you purchase 5-10% more than you need for re-sorting and installation.



Wooden floor oak planks 3-layer country, 5G-C

Our Country engineered oak showcases a bold, expressive look with large cracks, bigger knots and areas of sapwood. All natural characteristics and color variations are fully allowed without limitation. Open cracks and knots are carefully filled.

light brushed

black filler

DESCRIPTION	
Length	1900 mm
Width	190 mm
Thickness	14 mm



It is recommended that you purchase 5-10% more than you need for re-sorting and installation.



**AUTHORIZED
GLOBAL SELLER:**

zen
trade & consulting

CONTACT

☎ **(US)** +01 347 271-1952

☎ **(KOSOVO)** +383 (0) 45 280 680

✉ sales@zentradeandconsulting.com

📍 Rr. Shpetim Robaj, Nr. 3, Prishtinë 10000

🌐 www.zentradeandconsulting.com